



**POLYCAB INDIA LIMITED**

**LDC LP No. 01/2020-21 Dtd : 22nd June 2020**

**List of Products Covered in Our LDC LP**

**Coaxial Cables**

**Lan Cables**

**Telephone Switchboard Cables**

**Telephone Dry Armoured Cables**

**Submersible Cables**

**Single Core Flexible Cables**

**Multicore Flexible Cables**

**Single Core XLPE Unarmoured/Armoured Cables**

**CCTV Cables**

**Fire Alarm Cables**

**Solar Cables**

**BMS Cables**

**Braided Cables**

**Steel Braided Cables**

**Speaker Cables**

**Welding Cables**

**Aluminium Service Wires**

**Instrumentation Cables**

**Rubber Cables**

**JFTC Unarmoured/Armoured Cables**

**RS 485 Cables**

**Fire Survival Cables**

**Festoon Cables**

**Uninyvin Cables**

**Optical Fibre Cables**

**FS Aluminium Cables**



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES**

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Flexible Armoured
RG - 59	1845	5625	80000
RG - 6	2255	6885	86500
RG - 11	5120	15615	124000
RG-6 CCS	1665	5080	77500
RG-11 CCS	3360	10250	113000

**POLYCAB LAN (COMPUTER) CABLES**

Polycab 4 Pair <u>Unshielded</u> Twisted Pair (UTP) LAN (Computer) Cables			Polycab 4 Pair <u>Shielded</u> Twisted Pair (STP) LAN (Computer) Cables	
	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m
CAT 5 E	7300	89000	10350	101000
CAT 6	9125	100000	13000	111000
CAT 6 (A) - GOLD	10950		15600	



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES						POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES					
<p>Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification</p>						<p>Polycab PVC / Xlpe Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts as per IS:694/2010</p>					
						<p>No. of Pairs &amp; Size</p>		<p>Rate / 100 Mtr. (Rs.)</p>		<p>Rate / 90 Mtr (Rs.)</p>	
		<p>0.4 mm</p>	<p>0.5 mm</p>	<p>0.4 mm</p>	<p>0.5 mm</p>	<p>Master Packing</p>		<p>1.5</p>	<p>6900</p>	<p>7250</p>	<p>6650</p>
<p>1 Pair</p>		<p>620</p>	<p>825</p>	<p>560</p>	<p>745</p>	<p>20</p>		<p>2.5</p>	<p>11200</p>	<p>11700</p>	<p>10600</p>
<p>2 Pair</p>		<p>1025</p>	<p>1420</p>	<p>925</p>	<p>1280</p>	<p>20</p>		<p>4</p>	<p>16300</p>	<p>17000</p>	<p>15800</p>
<p>3 Pair</p>		<p>1510</p>	<p>2100</p>	<p>1360</p>	<p>1890</p>	<p>16</p>		<p>6</p>	<p>23900</p>	<p>25000</p>	<p>23200</p>
<p>4 Pair</p>		<p>2070</p>	<p>2745</p>	<p>1865</p>	<p>2470</p>	<p>12</p>		<p>10</p>	<p>40400</p>	<p>41500</p>	
<p>5 Pair</p>		<p>2545</p>	<p>3415</p>	<p>2290</p>	<p>3075</p>	<p>8</p>		<p>16</p>	<p>62800</p>	<p>63000</p>	
<p>10 Pair</p>			<p>6615</p>		<p>5955</p>	<p>1</p>		<p>25</p>	<p>98500</p>	<p>98900</p>	
<p>20 Pair</p>			<p>12400</p>		<p>11160</p>	<p>1</p>		<p>35</p>	<p>136200</p>	<p>136800</p>	
<p>50 Pair</p>			<p>29900</p>			<p>1</p>		<p>50</p>	<p>225900</p>	<p>244500</p>	
<p>100 Pair</p>			<p>58200</p>			<p>1</p>		<p>70</p>	<p>314500</p>	<p>340400</p>	
								<p>95</p>	<p>406000</p>	<p>439500</p>	
								<p>120</p>	<p>519100</p>	<p>562000</p>	
								<p>150</p>	<p>646700</p>	<p>700000</p>	
ARMOURED TELEPHONE CABLES											
<p>No. of Pairs</p>		<p>Rate / 100m (0.5mm)</p>				<p>Master Packing</p>					
<p>2 Pair</p>		<p>7075</p>				<p>Drums/Coils as required</p>					
<p>5 Pair</p>		<p>11000</p>				<p>Drums/Coils as required</p>					
<p>10 Pair</p>		<p>16200</p>				<p>Drums/Coils as required</p>					
<p>20 Pair</p>		<p>21500</p>				<p>Drums/Coils as required</p>					



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**Polycab FR Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

**Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		(Rate/100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	700	25	2145	2810	3640	4	4525	5450
0.75	24/.2	8	1020	25	2950	3850	4985	4	6370	7600
1	32/.2	13	1320	20	3565	4785	6130	4	7930	9325
1.5	30/.25	17	1925	16	4650	6455	8510	4	10900	13200
2.5	50/.25	24	3120	12	7480	10400	13600	3	17700	21500
4	56/.3	30	4770	8	11400	16000	20800		27700	33000
6	84/.3	38	7070	6	15500	23800	30100		42700	51000
10	80/.4	52	12300	1	27200	39900	52100		73200	
16	126/.4	70	18800	1	44100	62000	79400		116600	
25	196/.4	88	29600	1	71200	96900	128400		195500	
35	276/.4	110	41000	1	99200	134900	176600		270400	
50	396/.4	145	58300	1	139800	194200	253400		391500	
70	354/.5	215	84700	1	237100	279500	367800		546200	
95	484/.5	260	111500	1	261800	391700	506600		754000	
120	608/.5	305	143300	1	331400	488100	642300		979000	
150	750/.5	355	177000	1	414200	628900	825100		1199100	
185	925/.5	415	219500	1	510900	768400	1025700		1463400	
240	1210/.5	500	287000	1	662600	1002600	1326400		1928300	
300	1527/.5	585	363600	1	828200	1253300	1671100		2397900	
400	2036/.5	695	484800	1	1104300	1658500	2214200		3181200	



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6285	7105	8450	10100
0.75	24/.2	8	8650	9800	11900	14100
1	32/.2	13	10800	12200	15100	17900
1.5	30/.25	17	15000	17200	20900	24700
2.5	50/.25	24	24000	27300	33900	40300
4	56/.3	30	37600	42500	52800	62700
6	84/0.3	37	60000			

  

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	11600	13200	15300	20400
0.75	24/.2	8	16200	18500	21700	28700
1	32/.2	13	20500	23500	27900	36400
1.5	30/.25	17	28800	32800	38800	50400
2.5	50/.25	24	46700	53400	62400	82600

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables					CCTV Cables (Rate/90m)	
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables	CCTV Cables 4+1	CCTV Cables 3+1
mm <sup>2</sup>	No/mm		Rs/100 Mtr.	Rs/100 Mtr.	3750	3415
6	84/0.3	55	9200	12700	<b>CCTV Armoured Cables (Rate/Km.)</b>	
10	80/0.4	75	15500	21500	CCTV 4+1 Armoured	109000
16	126/0.4	103	23000	26900		
25	196/0.4	126	36500	41200		
35	276/0.4	152	49900	55300	<b>Fire Alarm System Arm Cables (Rate/Mtr.)</b>	
50	396/0.4	189	69600	76900	2 c x 1 Sq.mm. (Red)	94
70	354/0.5	240	96100	105700	2 c x 1.5 Sq.mm. (Red)	108
95	484/0.5	297	130000	135800		
120	608/0.5	346	164500	171700		
150	750/0.5	390	205600	214700		
185	925/0.5	460	250800	258600		
240	1210/0.5	552	325800	341100		
300	1527/0.5	640	406200	429100		
400	2036/0.5	753	541800	568700		



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

**Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		(Rate/100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	725	25	2300	3025	3915	4	4860	5850
0.75	24/.2	8	1055	25	3170	4135	5360	4	6850	8180
1	32/.2	13	1365	20	3830	5145	6590	4	8530	10000
1.5	30/.25	17	1995	16	4880	6775	8950	4	11400	13800
2.5	50/.25	24	3230	12	7855	10900	14300	3	18600	22600
4	56/.3	30	4935	8	12100	16800	21800		29000	34600
6	84/.3	38	7320	6	16300	25000	31600		44900	53600
10	80/.4	52	12700	1	28500	41800	54700		76900	
16	126/.4	70	19500	1	46200	65100	83400		122500	
25	196/.4	88	30600	1	74800	101800	134800		205300	
35	276/.4	110	42400	1	104100	141700	185500		283900	
50	396/.4	145	60400	1	146800	203800	266000		411100	
70	354/.5	215	87700	1	249000	293600	386300		573500	
95	484/.5	260	115500	1	274900	411300	531900		791700	
120	608/.5	305	148300	1	347900	512500	674400		1027900	
150	750/.5	355	183100	1	434900	660300	866400		1259100	
185	925/.5	415	227200	1	536400	806800	1077000		1536600	
240	1210/.5	500	297100	1	695800	1052800	1392800		2024700	
300	1527/.5	585	376400	1	869600	1315900	1754600		2517800	
400	2036/.5	695	501800	1	1159500	1741400	2324900		3340200	

**POLYCAB****POLYCAB INDIA LIMITED****LDC LP No. 01/2020-21 Dtd : 22nd June 2020****Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6750	7620	9065	10800
0.75	24/.2	8	9270	10500	12900	15100
1	32/.2	13	11600	13100	16300	19300
1.5	30/.25	17	15800	18000	22000	26000
2.5	50/.25	24	25100	28600	35500	42300
4	56/.3	30	39400	44700	55400	65900
6	84/0.3	37	63000			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	12600	14100	16500	21900
0.75	24/.2	8	17300	20000	23400	30900
1	32/.2	13	22000	25200	30000	39100
1.5	30/.25	17	30300	34400	40800	52800
2.5	50/.25	24	49000	56000	65500	86700



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB SOLAR WIRES / CABLES**

Flexible Tinned Copper Conductor/ Cross linkable (E Beam) LSZH Insulation/ Cross linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618		Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables		Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabalized PVC Sheathed Single Core Solar Cables	
Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m
4	5900	4	5500	4	5000
6	8300	6	8000	6	7400
10	16500	10	15800	10	13400
16	23900	16	23000	16	20700
25	39600	25	38000		
35	55400	35	53000		
50	79100	50	75800		
70	110800	70	106200		
95	150500	95	144100		
120	190000	120	182000		
150	237500	150	227600		
185	292900	185	280700		
240	380100	240	364100		
300	475000	300	455100		

**POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)**

Flexible Bare Copper Conductor, PVC Insulated,Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
2	4400	5400	6100	8000	12000
3	5400	6900	8100	10500	16300
4	6500	8500	9900	15000	23500
5	7800	11900	12000	16700	25500
6	8700	13400	14400	19200	30300
7	9500	13700	15800	21500	34300
8	11100	15200	17800	24300	38800
10	12900	17400	22000	30100	48900
12	15200	20400	26000	35900	57100
14	17600	23700	29800	40600	66200
16	20200	26900	33800	47000	75500
19	23000	31000	39000	54500	86800
24	27500	38000	49100	68800	112400

Packing - 100/300 Mtrs. Coils & 2000 Mtrs. Drums

Note : 3% Extra Charges for Drum Packing





**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB INDUSTRIAL BRAIDED CABLES**

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	0.5 Sq.mm.	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm	6 sq mm	10 sq.mm	16 sq.mm
2	6000	7100	8400	10400	14600	23300	33000	52100	78200
3	7400	8800	10400	13400	19000	28100	39600	64300	97600
4	8200	10800	12900	17100	24100	35600	50800	93300	145300
5	11800	14600	17400	21200	31800				
6	12800	16600	19800	23200	38300				
7	14600	17800	21500	27000	43900				
8	16000	20900	25000	32100	54400				
10	18500	25200	28900	38100	66100				
12	21700	28900	34000	43600	76900				
14	24800	33800	40800	52200	90000				
16	26700	40800	44500	58100	100200				
19	33800	45800	51600	66700	115500				
24	41500	53100	66100	84300	146600				
Cores	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.		
3	197500	261400	360100	505100	647800	853700	1064100		
4	251000	325200	457300	632200	833500	1067100	1329100		



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)**

**Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.**

Cores	0.5 Sq.mm.	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm	6 sq mm
2	6900	8000	9000	11300	16000	22400	30600
3	8000	9900	11300	14400	20900	29700	42000
4	9700	11800	13800	17900	26200	39900	56800
5	11000	14000	16800	21500	31600		
6	12700	16200	19000	24900	37200		
7	13500	17700	20900	27600	41600		
8	15300	19900	23700	31400	47600		
10	18600	24500	28800	38300	58600		
12	20900	28100	33400	44600	68900		
14	24000	31400	37800	51300	78700		
16	26700	35800	43000	57900	89400		
19	30400	41400	50100	67500	104600		
24	38500	51300	62500	85400	131000		

Cores	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.	70 Sq.mm	95 Sq.mm.
2	49500	73200	111000	150700	213100	291400	389000
3	68900	103000	157300	214900	304300	419300	559700
4	93900	141800	218200	298500	424100	585000	783700

**Note : 3% Extra Charges for Drum Packing**

**POLYCAB INDUSTRIAL SPEAKER WIRES**

**Speaker Wires (Oxygen Free) (Rate per 90 mtr)**

Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.
23/36	1775	23/38	1255	0.5 Sq.mm	1630	1.5 Sq.mm	4265
40/36	2795	40/38	2090	0.75 Sq.mm	2300	2 Sq.mm	6320
70/36	4895	70/38	3275	1 Sq.mm	2980	2.5 Sq.mm	6960

**\*\* Flame Retardant, Heat Resistant up to 90°C & Oil Resistant**

**POLYCAB INDUSTRIAL WELDING CABLES**

**Polycab Flexible Copper Conductor 1100 Volts Welding Cable**

Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	HOFr Insulation Rate/100m (Rs)
16	120	509/0.2	28400
25	160	796/0.2	41600
35	230	1115/0.2	58000
50	400	703/0.3	82500
70	600	999/0.3	115000
95	700	1346/0.3	155200
120	1100	1699/0.3	191600



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB ALUMINIUM WIRES & CABLES**

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	435	1.5	445	2	1.5	1610
2.5	670	2.5	680	2	2.5	2280
4	880	4	920	2	4	3220
6	1340	6	1380	2	6	4210
10	1990	10	2070	2	10	6530
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2980	2	16	8650
		25	4635	2	25	12300
		35	6250	2	35	15700
		50	8400	2	50	19900
SQ.MM	RATE/ 100M	70	11200	2	70	19900
1.5	660	95	13100	3	1.5	2200
2.5	815	120	19000	3	2.5	3300
4	1550	150	23600	3	4	4500
6	2110	185	29300	3	6	6400
10	2890	240	38100	3	10	9300
16	4110	300	47500	3	16	12700
25	5985	400	61000	3	25	17700
35	7630	500	77600	3	35	23100
50	10100	630	98300	3	50	29300
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				POLYCAB <u>XLPE</u> INSULATED AND PVC <u>SHEATHED</u> CABLE WITH EACH CORE HAVING <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.		
NO.OF CORES	SQ.MM		RATE/ 100M	NO.OF CORES	SQ.MM	RATE/100M
2	1.5		1495	2	4	2980
2	2.5		2185	2	6	4230
2	4		2980	2	10	5255
2	6		4135	2	16	7655
2	10		6350			
3	1.5		2070			
3	2.5		3220			
3	4		4665			
3	6		5900			
3	10		9060			



POLYCAB INDIA LIMITED

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)  
Round/Strip Armoured PVC Outer Sheathed Instrumentation

OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	84	0.75	97	1	106	1.5	127	2.5	171
CORE	3	0.5	97	0.75	112	1	128	1.5	160	2.5	217
CORE	4	0.5	111	0.75	131	1	153	1.5	193	2.5	269
CORE	5	0.5	124	0.75	149	1	176	1.5	225	2.5	318
CORE	6	0.5	140	0.75	169	1	202	1.5	259	2.5	372
CORE	7	0.5	148	0.75	182	1	219	1.5	283	2.5	411
CORE	8	0.5	167	0.75	205	1	246	1.5	321	2.5	465
CORE	10	0.5	195	0.75	242	1	296	1.5	386	2.5	568
CORE	12	0.5	216	0.75	272	1	335	1.5	444	2.5	638
CORE	14	0.5	239	0.75	306	1	376	1.5	505	2.5	737
CORE	16	0.5	264	0.75	340	1	423	1.5	568	2.5	827
CORE	19	0.5	299	0.75	386	1	483	1.5	653	2.5	964
CORE	24	0.5	362	0.75	474	1	576	1.5	793	2.5	1201
PAIR	1	0.5	84	0.75	97	1	106	1.5	127	2.5	171
PAIR	2	0.5	123	0.75	146	1	165	1.5	206	2.5	293
PAIR	3	0.5	146	0.75	178	1	207	1.5	266	2.5	385
PAIR	4	0.5	171	0.75	215	1	253	1.5	329	2.5	484
PAIR	5	0.5	199	0.75	252	1	300	1.5	394	2.5	577
PAIR	6	0.5	227	0.75	291	1	346	1.5	459	2.5	677
PAIR	7	0.5	246	0.75	318	1	383	1.5	513	2.5	765
PAIR	8	0.5	277	0.75	361	1	436	1.5	575	2.5	866
PAIR	10	0.5	331	0.75	422	1	517	1.5	696	2.5	1065
PAIR	12	0.5	372	0.75	488	1	602	1.5	815	2.5	1249
PAIR	14	0.5	402	0.75	549	1	680	1.5	933	2.5	1436
PAIR	16	0.5	456	0.75	616	1	766	1.5	1045	2.5	1628
PAIR	19	0.5	516	0.75	713	1	889	1.5	1220	2.5	1904
PAIR	24	0.5	644	0.75	890	1	1102	1.5	1531	2.5	2392
TRIAD	1	0.5	100	0.75	117	1	129	1.5	162	2.5	221
TRIAD	2	0.5	156	0.75	192	1	215	1.5	276	2.5	400
TRIAD	3	0.5	192	0.75	243	1	278	1.5	366	2.5	541
TRIAD	4	0.5	230	0.75	298	1	347	1.5	459	2.5	680
TRIAD	5	0.5	267	0.75	354	1	413	1.5	555	2.5	826
TRIAD	6	0.5	308	0.75	410	1	482	1.5	641	2.5	973
TRIAD	7	0.5	339	0.75	454	1	540	1.5	723	2.5	1106
TRIAD	8	0.5	381	0.75	500	1	605	1.5	821	2.5	1263
TRIAD	10	0.5	453	0.75	618	1	733	1.5	1009	2.5	1556
TRIAD	12	0.5	515	0.75	711	1	858	1.5	1178	2.5	1842
TRIAD	14	0.5	585	0.75	812	1	984	1.5	1354	2.5	2122
TRIAD	16	0.5	649	0.75	906	1	1103	1.5	1533	2.5	2406
TRIAD	19	0.5	751	0.75	1052	1	1286	1.5	1792	2.5	2821
TRIAD	24	0.5	928	0.75	1315	1	1609	1.5	2257	2.5	3551
QUAD	1	0.5	113	0.75	134	1	155	1.5	195	2.5	273



POLYCAB INDIA LIMITED

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	48	0.75	59	1	70	1.5	82	2.5	115
PAIR	2	0.5	76	0.75	95	1	115	1.5	162	2.5	220
PAIR	3	0.5	100	0.75	127	1	162	1.5	209	2.5	313
PAIR	4	0.5	115	0.75	162	1	209	1.5	267	2.5	406
PAIR	5	0.5	151	0.75	198	1	291	1.5	323	2.5	501
PAIR	6	0.5	173	0.75	220	1	313	1.5	394	2.5	590
PAIR	7	0.5	186	0.75	254	1	323	1.5	439	2.5	683
PAIR	8	0.5	209	0.75	279	1	382	1.5	501	2.5	777
PAIR	10	0.5	254	0.75	361	1	464	1.5	626	2.5	973
PAIR	12	0.5	304	0.75	416	1	546	1.5	742	2.5	1146
PAIR	14	0.5	335	0.75	476	1	626	1.5	846	2.5	1320
PAIR	16	0.5	394	0.75	531	1	718	1.5	973	2.5	1505
PAIR	19	0.5	452	0.75	636	1	833	1.5	1135	2.5	1772
PAIR	24	0.5	557	0.75	787	1	1041	1.5	1426	2.5	2245
TRIAD	1	0.5	65	0.75	73	1	92	1.5	113	2.5	167
TRIAD	2	0.5	107	0.75	130	1	163	1.5	210	2.5	312
TRIAD	3	0.5	142	0.75	174	1	221	1.5	291	2.5	440
TRIAD	4	0.5	175	0.75	219	1	283	1.5	373	2.5	575
TRIAD	5	0.5	212	0.75	265	1	346	1.5	459	2.5	715
TRIAD	6	0.5	247	0.75	313	1	408	1.5	546	2.5	847
TRIAD	7	0.5	279	0.75	354	1	465	1.5	624	2.5	974
TRIAD	8	0.5	317	0.75	405	1	529	1.5	718	2.5	1110
TRIAD	10	0.5	388	0.75	499	1	662	1.5	889	2.5	1380
TRIAD	12	0.5	452	0.75	590	1	778	1.5	1051	2.5	1638
TRIAD	14	0.5	517	0.75	678	1	898	1.5	1213	2.5	1896
TRIAD	16	0.5	591	0.75	769	1	1019	1.5	1380	2.5	2167
TRIAD	19	0.5	690	0.75	899	1	1195	1.5	1621	2.5	2555
TRIAD	24	0.5	862	0.75	1128	1	1499	1.5	2053	2.5	3217
QUAD	1	0.5	70	0.75	87	1	111	1.5	151	2.5	220

**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB INSTRUMENTATION CABLES**

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

**INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	162	0.75	176	1	203	1.5	247	2.5	339
PAIR	3	0.5	199	0.75	222	1	259	1.5	320	2.5	449
PAIR	4	0.5	237	0.75	271	1	317	1.5	400	2.5	556
PAIR	5	0.5	277	0.75	319	1	378	1.5	465	2.5	671
PAIR	6	0.5	318	0.75	371	1	439	1.5	550	2.5	786
PAIR	7	0.5	350	0.75	410	1	488	1.5	617	2.5	889
PAIR	8	0.5	398	0.75	452	1	546	1.5	699	2.5	1015
PAIR	10	0.5	470	0.75	553	1	666	1.5	856	2.5	1245
PAIR	12	0.5	534	0.75	634	1	769	1.5	1000	2.5	1467
PAIR	14	0.5	609	0.75	723	1	880	1.5	1139	2.5	1685
PAIR	16	0.5	682	0.75	814	1	990	1.5	1285	2.5	1907
PAIR	19	0.5	780	0.75	935	1	1144	1.5	1500	2.5	2228
PAIR	24	0.5	973	0.75	1175	1	1437	1.5	1892	2.5	2803
TRIAD	2	0.5	190	0.75	220	1	248	1.5	310	2.5	425
TRIAD	3	0.5	237	0.75	281	1	324	1.5	412	2.5	582
TRIAD	4	0.5	289	0.75	348	1	403	1.5	505	2.5	741
TRIAD	5	0.5	340	0.75	413	1	483	1.5	616	2.5	908
TRIAD	6	0.5	393	0.75	470	1	555	1.5	722	2.5	1067
TRIAD	7	0.5	435	0.75	524	1	623	1.5	817	2.5	1212
TRIAD	8	0.5	485	0.75	602	1	707	1.5	933	2.5	1383
TRIAD	10	0.5	583	0.75	727	1	866	1.5	1145	2.5	1719
TRIAD	12	0.5	676	0.75	846	1	1012	1.5	1337	2.5	2015
TRIAD	14	0.5	763	0.75	961	1	1161	1.5	1543	2.5	2321
TRIAD	16	0.5	857	0.75	1083	1	1302	1.5	1745	2.5	2633
TRIAD	19	0.5	993	0.75	1259	1	1529	1.5	2052	2.5	3085
TRIAD	24	0.5	1245	0.75	1584	1	1928	1.5	2564	2.5	3905



POLYCAB INDIA LIMITED

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIEDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	100	0.75	115	1	141	1.5	173	2.5	244
PAIR	3	0.5	127	0.75	162	1	198	1.5	244	2.5	349
PAIR	4	0.5	162	0.75	198	1	244	1.5	313	2.5	452
PAIR	5	0.5	198	0.75	244	1	304	1.5	382	2.5	557
PAIR	6	0.5	232	0.75	291	1	361	1.5	452	2.5	662
PAIR	7	0.5	267	0.75	323	1	406	1.5	510	2.5	754
PAIR	8	0.5	304	0.75	370	1	464	1.5	590	2.5	869
PAIR	10	0.5	370	0.75	464	1	579	1.5	730	2.5	1065
PAIR	12	0.5	430	0.75	546	1	672	1.5	855	2.5	1274
PAIR	14	0.5	510	0.75	626	1	787	1.5	995	2.5	1471
PAIR	16	0.5	569	0.75	708	1	881	1.5	1135	2.5	1678
PAIR	19	0.5	662	0.75	833	1	1041	1.5	1331	2.5	1982
PAIR	24	0.5	833	0.75	1041	1	1310	1.5	1678	2.5	2490
TRIAD	2	0.5	137	0.75	155	1	188	1.5	237	2.5	342
TRIAD	3	0.5	182	0.75	212	1	261	1.5	330	2.5	484
TRIAD	4	0.5	230	0.75	271	1	335	1.5	428	2.5	636
TRIAD	5	0.5	279	0.75	327	1	408	1.5	523	2.5	782
TRIAD	6	0.5	324	0.75	386	1	483	1.5	628	2.5	928
TRIAD	7	0.5	368	0.75	439	1	553	1.5	718	2.5	1067
TRIAD	8	0.5	418	0.75	508	1	636	1.5	820	2.5	1218
TRIAD	10	0.5	523	0.75	625	1	784	1.5	1015	2.5	1523
TRIAD	12	0.5	613	0.75	734	1	925	1.5	1197	2.5	1807
TRIAD	14	0.5	705	0.75	846	1	1067	1.5	1385	2.5	2091
TRIAD	16	0.5	793	0.75	959	1	1211	1.5	1574	2.5	2377
TRIAD	19	0.5	928	0.75	1124	1	1424	1.5	1863	2.5	2782
TRIAD	24	0.5	1163	0.75	1421	1	1800	1.5	2342	2.5	3525



# POLYCAB INDIA LIMITED

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

## ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						326	489	660	921
2 Core	121	174	234	345	547	789			
3 Core	155	221	305	455	726	1068	1657	2225	3103
4 Core	192	279	389	594	931	1381	2149	2869	4011
5 Core	229	329	526	744	1184	1762	2646	3616	5013
6 Core	274	395	615	849	1352	2007	3285	4287	6023
7 Core	300	434	684	947	1515	2264	3553	4855	6851
8 Core	345	552							
10 Core	468	686							
12 Core	539	792							
14 Core	626	907							
16 Core	702	1013							
19 Core	807	1173							
24 Core	1031	1525							

## ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	1252	1673	2104	2591	3177	4077	5055	6675	
3 Core	4163	5557	6922	8563	10520	13495	16753	22076	
4 Core	5420	7225	9029	11180	13734	17660	21947	29188	





**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	70	106	173	411	752	1474

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	118	179	258	527	908	1690

**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB RS 485 CABLES (Armoured)**500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	107
	22 AWG	0.32	113
	20 AWG	0.50	123
	18 AWG	0.80	137
	17 AWG	1.00	150
2 Pair	24 AWG	0.205	145
	22 AWG	0.32	161
	20 AWG	0.50	177
	18 AWG	0.80	217
	17 AWG	1.00	239

**POLYCAB RS 485 CABLES (Un Armoured)**500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	56
	22 AWG	0.32	64
	20 AWG	0.50	70
	18 AWG	0.80	86
	17 AWG	1.00	96
2 Pair	24 AWG	0.205	88
	22 AWG	0.32	102
	20 AWG	0.50	113
	18 AWG	0.80	147
	17 AWG	1.00	166

**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**POLYCAB RS 485 CABLES (Armoured)**500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	118
	22 AWG	0.32	124
	20 AWG	0.50	135
	18 AWG	0.80	151
	17 AWG	1.00	165
2 Pair	24 AWG	0.205	160
	22 AWG	0.32	177
	20 AWG	0.50	195
	18 AWG	0.80	239
	17 AWG	1.00	263

**POLYCAB RS 485 CABLES (Un Armoured)**500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	62
	22 AWG	0.32	70
	20 AWG	0.50	77
	18 AWG	0.80	95
	17 AWG	1.00	106
2 Pair	24 AWG	0.205	97
	22 AWG	0.32	112
	20 AWG	0.50	124
	18 AWG	0.80	162
	17 AWG	1.00	183



**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed  
Fire Survival Cables**

					Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores	
1.5	217	271		330	
2.5	271	346		427	
4	318	417		522	
6	412	552		698	
10	583	797		1019	
16	773	1079		1420	
25	1102	1588	1912	2086	
35	1466	2127	2459	2808	
50	1933	2825	3313	3740	
70	2686	3946	4617	5226	
95	3531	5198	6072	6889	
120	4393	6495	7739	8625	
150	5379	7965	9203	10569	
185	6645	9850	11531	13067	
240	8449	12550	14667	16665	
300	10467	15551	18148	20670	
400	13626	20271	23494	26946	



**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outsheathed Fire Survival Cables**

					Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores	
1.5	243	298		361	
2.5	298	375		459	
4	347	446		555	
6	442	584		734	
10	618	833		1060	
16	806	1114		1465	
25	1144	1633	1962	2138	
35	1511	2177	2514	2866	
50	1983	2881	3374	3810	
70	2748	4018	4695	5310	
95	3601	5275	6157	6982	
120	4467	6580	7842	8735	
150	5468	8069	9319	10699	
185	6745	9973	11670	13219	
240	8570	12699	14834	16849	
300	10609	15724	18342	20891	
400	13804	20492	23742	27218	



**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables**

					Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores	
1.5	252	312		377	
2.5	308	390		479	
4	357	462		575	
6	454	602		757	
10	631	854		1087	
16	822	1139		1498	
25	1170	1673	2009	2191	
35	1541	2221	2566	2925	
50	2021	2938	3444	3886	
70	2797	4092	4784	5409	
95	3655	5357	6258	7091	
120	4534	6680	7966	8869	
150	5554	8198	9473	10872	
185	6856	10139	11862	13438	
240	8701	12898	15067	17114	
300	10765	15957	18619	21203	
400	13999	20784	24091	27608	



# POLYCAB INDIA LIMITED

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

## FESTOON CABLES

(Rate/Mtr.)

Cores	0.5	0.75	1	1.5	2.5	4	6	10	16	25	35
3	43	55	68	89	143	218	317	528	818	1298	1779
4	56	72	90	119	190	290	425	707	1093	1728	2369
5	73	95	119	156	245	378					
6	87	113	141	184	297	454					
7	100	131	164	214	344	527					
8	115	149	185	247	396	607					
9	134	176	218	283	458	692					
10	148	193	241	313	507	774					
12	175	230	286	372	604	921					
14	212	270	337	445	709	1082					
16	240	313	389	504	814	1241					
18	263	343	435	564	901	1375					
24	358	467	590	764	1215	1867					

**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**UNINYVIN CABLES****Multistranded Annealed Tinned Copper Conductor 105° C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables**

Cable Size	Nom. Conductor Area (Sq.mm.)	Rate Per Mtr.
22	0.347	15.40
20	0.556	20.00
18	0.966	29.70
16	1.17	35.10
14	2.05	54.00
12	3.22	78.30
10	5.33	111
8	8.76	173
6	13.30	257
4	21.50	405
2	33.30	621
1	40.70	751
0	53.00	975
00	68.30	1242
000	84.20	1539
0000	109	1979





**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**UNI-TUBE UN-ARMoured OPTICAL FIBRE CABLES**

<b>Cable Type</b>	<b>Fiber Type</b>	<b>Rate. Per Km.</b>
2F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	20250
4F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	23500
6F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	26500
8F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	32400
12F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	37850
6F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	47500
12F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	81000

**UNI-TUBE ARMoured OPTICAL FIBRE CABLES**

<b>Cable Type</b>	<b>Fiber Type</b>	<b>Rate. Per Km.</b>
24F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	152000



**POLYCAB INDIA LIMITED**

LDC LP No. 01/2020-21 Dtd : 22nd June 2020

**FS Aluminium Power Cables**

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/XIpe Insulation/Wrapped with Fibre Tape Barrier/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	424	548
25	571	728
35	691	892
50	855	1109
70	1169	1521
95	1461	1901
120	1746	2288
150	2077	2721
185	2517	3288
240	3133	4097
300	3770	4949
400	4692	6146

• The above rates are exclusive of GST which shall be charged extra.